AVK SWING CHECK VALVES WITH LEVER SPRING
PRESSURE LOSS, DN50, DN65, DN80 AND DN100



These curves are based on tests, performed according to EN1267, with a horizontal installation.

DN50, fully open check valve at approx. 25m³/hr (3,54m/s) - DN65, fully open check valve at approx. 35m³/hr (2,93m/s) - DN80, fully open check valve at approx. 45m³/hr (2,49m/s) - DN100, fully open check valve at approx. 50m³/hr (1,77m/s)

COPYRIGHT©AVK GROUP A/S 2026 - AVK INTERNATIONAL A/S, Bizonvej 1, DK-8464 Galten - www.avkvalves.eu

AVK SWING CHECK VALVES WITH LEVER SPRING
PRESSURE LOSS, DN125, DN150 AND DN200



These curves are based on tests, performed according to EN1267, with a horizontal installation.

DN125, fully open check valve at approx. 43m³/hr (0,97m/s) - DN150, fully open check valve at approx. 70m³/hr (1,10m/s) - DN200, fully open check valve at approx. 130m³/hr (1,15m/s)

COPYRIGHT©AVK GROUP A/S 2026 - AVK INTERNATIONAL A/S, Bizonvej 1, DK-8464 Galten - www.avkvalves.eu

AVK SWING CHECK VALVES WITH LEVER SPRING
PRESSURE LOSS, DN250 AND DN300



These curves are based on tests, performed according to EN1267, with a horizontal installation.
DN 250, fully open check valve at approx. 225 m³/hr (1,27m/s) - DN300, fully open check valve at approx. 330m³/hr (1,30m/s)

COPYRIGHT©AVK GROUP A/S 2026 - AVK INTERNATIONAL A/S, Bizonvej 1, DK-8464 Galten - www.avkvalves.eu